





### FULL-SIZE EXCAVATORS

Specifications	CX130B	CX160B	CX210B	CX240B	CX290B
Engine - hp (kW)	95 (71)	120 (89.2)	157 (117)	177 (132)	207 (154)
Dig Depth	19 ft 10 in (6.1 m)	21 ft 4 in (6.5 m)	21 ft 10 in (6.7 m)	24 ft 4 in (7.4 m)	24 ft 11 in (7.6 m)
Operating Weight - lb (kg)	27,800 (12 610)	37,700 (17 100)	47,400 (21 500)	55,120 (25 000)	65,697 (29 800)
Bucket Digging Force - lb (kN)	21,357 (95)	26,527 (118)	34,171 (152)	39,117 (174)	42,759 (190)
Specifications	CX350B	CX470B	CX700B	CX800B	
Engine - hp (kW)	271 (202)	362 (270)	463 (345)	532 (397)	
Dig Depth	26 ft 8 in (8.1 m)	27 ft 4 in (8.3 m)	32 ft 4 in (9.9 m)	35 ft 0 in (10.7 m)	
Operating Weight - lb (kg)	79,065 (35 863)	103,800 (47 083)	153,400 (69 581)	178,575 (81 000)	
Bucket Digging Force - lb (kN)	55,843 (248.4)	60,698 (270)	71,260 (317)	81,156 (361)	

### ARTICULATED TRUCKS

Specifications	327B	330B	335B	340B
Engine - hp (kW)	300 (224)	334 (249)	380 (284)	426 (318)
Payload - lb (kg)	51,147 (23 200)	62,082 (28 160)	69,445 (31 500)	79,366 (36 000)
Heaped Capacity - cu yd (m³)	18 (14.5)	23 (17.6)	26.2 (20)	28.8 (22)
Total Laden Weight - lb (kg)	100,905 (45 770)	111,840 (50 730)	132,277 (60 000)	143,300 (65 000)



### MINIMUM SWING EXCAVATORS



Specifications	CX75	CX80	CX135	CX225
Engine - hp (kW)	54 (40)	54 (40)	95 (70.9)	153 (114.4)
Dig Depth	14 ft 11 in (4.5 m)	15 ft 1 in (4.6 m)	19 ft 5 in (5.9 m)	22 ft 0 in (6.7 m)
Operating Weight - lb (kg)	17,468 (7919)	18,585 (8430)	29,631 (13440)	53,223 (24 141)
Bucket Digging Force - lb (kN)	12,792 (56.9)	12,792 (56.9)	20,165 (89.7)	31,698 (141)

### COMPACT AND FULL-SIZE WHEEL LOADERS



Specifications	COMPACT WHEEL LOADERS				FULL-SIZE WHEEL LOADERS				
	21E	121E	221E	321E	521E	621E	721E	821E	1221E
Engine Max Power - hp (kW)	50 (38)	60 (45)	69 (51)	77 (57)	135 (101)	162 (121)	183 (137)	213 (159)	320 (239)
Operating Weight - lb (kg)	10,173 (4615)	10,849 (4921)	11,947 (5419)	12,676 (5750)	23,069 (10 464)	27,406 (12 431)	30,644 (13 900)	37,844 (17 166)	65,600 (29 755)
Bucket Capacity - cu yd (m3)	1.1 (0.8)	1.2 (0.9)	1.3 (1.0)	1.4 (1.1)	2.6 (2.0)	3.0 (2.3)	3.5 (2.7)	4.5 (3.4)	7.6 (5.7)
Breakout Force - lb (kg)	8,336 (3804)	10,024 (4547)	10,189 (4622)	11,982 (5435)	20,926 (9492)	26,577 (12 055)	32,958 (14 950)	40,738 (18 479)	54,584 (24 759)



## COMPACT EXCAVATORS



Specifications	CX17B	CX27B	CX31B	CX36B	CX50B
Engine - hp (kW)	15.2 (11.3)	21.3 (15.9)	28.4 (21.2)	28.4 (21.2)	39.8 (29.3)
Dig Depth	7 ft 1 in (2.2 m)	8 ft 4 in (2.5 m)	9 ft 2 in (2.8 m)	10 ft 1 in (3.1 m)	11 ft 9 in (3.6 m)
Operating Weight - lb (kg)	3,638 (1650)	5,556 (2520)	6,679 (3030)	7,958 (3610)	10,261 (4660)
Bucket Digging Force - lb (kg)	3,417 (1550)	6,351 (2881)	8,430 (3824)	8,430 (3824)	11,128 (5048)



## CRAWLER DOZERS

Specifications	550H	650K	750L	850L	1150K	1650L	1850K
Engine - hp (kW)	67 (50)	74.8 (56)	84 (63)	96 (72)	118 (88)	144 (107)	199 (148)
Operating Weight - lb (kg)	14,960 (6786)	19,400 (8813)	20,200 (9157)	20,700 (9402)	29,365 (13 317)	37,578 (17 042)	49,450 (22 430)
Blade Capacity - cu yd (m3)	1.9 (1.5)	2.6 (2.0)	2.6 (2.0)	2.7 (2.1)	4.2 (3.2)	4.2 (3.2)	7.3 (5.6)
Track on Ground - in. (m)	78 (2.0)	88 (2.2)	89 (2.3)	93 (2.4)	102 (2.6)	120 (3.0)	126 (3.2)

## LOADER/BACKHOES

Specifications	580M	580 Super M	580 Super M+	590 Super M	590 Super M+
Engine - hp (kW)	79 (59)	97 (72)	97 (72)	108 (81)	108 (81)
Backhoe Dig Depth	14 ft 3 in (4.3 m)	14 ft 5 in (4.4 m)	14 ft 10 in (4.5 m)	15 ft 11 in (4.9 m)	14 ft 10 in (4.5 m)
Loader Lift Capacity - lb (kg)	6,182 (2804)	6,182 (2804)	6,182 (2804)	7,327 (3323)	7,327 (3323)
Operating Weight - lb (kg)	16,510 (7489)	17,545 (7958)	18,128 (8223)	19,578 (8881)	19,578 (8881)



## SKID STEERS

Specifications	410	420	430	435	440	445	450	465
Engine - hp (kW)	57 (42)	69 (52)	77 (57)	77 (57)	83 (62)	77 (57)	83 (62)	83 (62)
Operating Weight - lb (kg)	5,430 (2463)	6,605 (2996)	6,800 (3084)	6,780 (3075)	7,040 (3193)	8,120 (3683)	8,630 (3915)	8,875 (4026)
Bucket Breakout Force - lbf (N)	4,654 (20 702)	5,500 (24 465)	5,784 (25 728)	6,300 (28 024)	6,207 (27 610)	7,400 (32 916)	7,213 (32 085)	7,400 (32 916)
Operating Load - lb (kg)	1,500 (681)	1,850 (839)	2,000 (907)	2,200 (998)	2,200 (998)	2,500 (1134)	2,450 (1111)	3,000 (1361)

## COMPACT TRACK LOADERS



Specifications	420CT	440CT	445CT	450CT
Engine - hp (kW)	69 (42)	83 (62)	77 (57)	83 (62)
Operating Weight - lb (kg)	8,340 (3783)	8,925 (4048)	10,200 (4626)	10,925 (4955)
Bucket Breakout Force - lbf (N)	5,503 (24 479)	7,400 (32 917)	6,700 (29 803)	6,200 (27 578)
Operating Load - lb (kg)	2,000 (907)	2,100 (952)	2,310 (1048)	2,700 (1225)

## COMPACTION



Specifications	DV201	DV202	DV204	SV208	SV210	SV212	SV216
Engine - hp (kW)	31 (23)	31 (23)	48 (36)	99 (73.8)	99 (73.8)	148 (110)	148 (110)
Operating Weight - lb (kg)	5,510 (2500)	5,950 (2700)	7,720 (3500)	15,741 (7140)	19,445 (8820)	25,386 (11 515)	31,479 (14 274)
Wheelbase - in. (m)	67.6 (1.7)	67.6 (1.7)	67.6 (1.7)	101 (2.6)	101 (2.6)	111 (2.8)	111 (2.8)
Drum Width - in. (m)	39.5 (1.0)	47.2 (1.2)	51.2 (1.3)	66 (1.7)	66 (1.7)	87 (2.2)	87 (2.2)



# YOU CAN COUNT ON CASE



You can count on Case and your Case dealer for full-service solutions—productive equipment, expert advice, flexible financing, genuine Case parts and fast service. We're here to provide you with the ultimate ownership experience.

## Case pride

You can take pride in the Case name on your machine. It's backed by more than a century of productivity and performance. Case and your Case dealer are here for you, not only when you buy the machine, but also after you put 1,000 or 10,000 hours on it.

## A rich, proud history

Case Construction Equipment's heritage spans more than 165 years. Growing from J.I. Case's innovations with steam-powered machinery in the late 1800s, Case developed road-building equipment that helped create early 20th century streets and highways across the world. By 1912, Case was well on its way to establishing itself as a full-line equipment manufacturer. The company continued to expand its construction equipment business over the years.

## Celebrating a tradition of innovation

In 1957, Case produced the world's first integrated loader/backhoe made and warranted by one manufacturer. Over the decades and into the 21st century, Case has continued to develop a long line of industry firsts and has taken a leadership role in pioneering new products and solutions. Today, Case produces 15 lines of equipment and more than 90 models to meet your toughest construction challenges. Supported by manufacturing and sales in more than 150 countries, Case serves the needs of our customers worldwide.

## Coast-to-coast customer support

In North America, Case equipment is sold and serviced by more than 350 dealer locations. No matter where you work, we're here to support and protect your investment and exceed your expectations.

To locate a Case dealer or learn more about Case equipment, go to [www.casece.com](http://www.casece.com) or for customer service call **1-866-54CASE6**.

It all adds up. You can count on Case.

NOTE: All engines meet current EPA emission regulations. NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

IMPORTANT: Case Construction Equipment Inc. reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your Case dealer/distributor will be able to give you details of the products and their specifications available in your area.

Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs and use any safety features provided.

©2008 CNH America LLC. All rights reserved. Case is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. Printed in U.S.A.

Form No. CCE9090802



Contains 10% Post-Consumer Fiber



## TELESCOPIC HANDLERS

Specifications	TX742	TX842	TX945
Engine - hp (kW)	88 (65)	107 (79)	107 (79)
Max Lift Capacity - lb (kg)	6,600 (2994)	8,000 (3628)	9,000 (4082)
Max Lift Height - ft (m)	42 (12.8)	42 (12.8)	45 (13.7)
Operating Weight - lb (kg)	22,700 (10 297)	24,930 (11 308)	27,778 (12 600)

## ROUGH-TERRAIN FORKLIFTS

Specifications	586G	588G
Engine - hp (kW)	80 (60)	80 (60)
Lift Capacity - lb (kg)	6,000 (2722)	8,000 (3628)
Operating Weight - lb (kg)	13,003 (5897)	17,545 (7958)



## MOTOR GRADERS

Specifications	845 DHP	865 VHP	885
Engine - hp (kW)	140/160 (104/119)	180/190/205 (134/142/153)	205 (153)
Blade Length (Standard) ft (m)	12 (3.7)	13 (4.0)	14 (4.3)
Operating Weight - lb (kg)	29,777 (13 535)	32,265 (14 635)	37,950 (17 250)

## LOADER/TOOL CARRIERS

Specifications	570M XT
Engine - hp (kW)	79 (59)
Loader Lift Capacity - lb (kg)	6,503 (2956)
Operating Weight - lb (kg)	10,537 (4779)

